

Page 1/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.03.2020 Version number 12 Revision: 17.03.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name HK-LASUR / HK Stain

Article number: 2250-94

1.2 Relevant identified uses of the substance or mixture and uses advised against

Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services,

craftsmen)

Product category PC8 Biocidal products

Process category

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC10 Roller application or brushing

Environmental release category

ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

ERC8f Widespread use leading to inclusion into/onto article (outdoor)

ERC10a Widespread use of articles with low release (outdoor)

Application of the substance / the mixture Wood protection glazing

Uses advised against No further relevant information available.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Remmers GmbH Postfach 1255

D-49624 Löningen / Germany

Tel.: +49(0)5432/83-0

Fax: +49(0)5432/3985
Information department:

Product Safety department: Tel.: Steve Dunn Tel.: +44 (0) 1293 594 010

E-Mail: sales@remmers.co.uk

1.4 Emergency telephone number:

during working hours:

U.K.: Tel.: +44 (0) 1293 594 010

sales@remmers.co.uk

Head Office Germany: Tel.: +49 (0)5432 83 187

info@remmers.de

after working hours: Tel.: +49 (0)171 21 34 091

24h-Transport Emergency Contact Phone Number:

within USA and Canada: 1-800-424-9300 outside USA and Canada: 001-703-527-3887

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)

Remmers (UK) Limited

Unit B1 The Fleming Centre

West Sussex RH10 9NN

fon +44 (0) 1293 594 010

fax +44 (0) 1293 594 037

Printing date 17.03.2020 Version number 12 Revision: 17.03.2020

Trade name HK-LASUR / HK Stain

(Contd. of page 1)

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



Signal word Danger

Hazard-determining components of labelling:

isoparaffine hydrocarbon mixture

hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics

Solvent naphtha (petroleum), heavy arom.

hydrocarbons, C9, aromatics

Hazard statements

H304 May be fatal if swallowed and enters airways.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P273 Avoid release to the environment.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains cobalt(II) 2-ethylhexanoate, 3-iodo-2-propynyl butylcarbamate, 2-butanone oxime. May produce an allergic reaction.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

Description: Mixture of the substances listed below with harmless additions.

Dangerous components:		
EC number: 918-481-9 Index number: 649-327-00-6 Reg.nr.: 01-2119457273-39-XXXX	isoparaffine hydrocarbon mixture Asp. Tox. 1, H304	40-60%
EC number: 920-360-0 Reg.nr.: 01-2119448343-41-XXXX	hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics Asp. Tox. 1, H304	20-40%
	cobalt(II) 2-ethylhexanoate Repr. 2, H361f; Aquatic Acute 1, H400; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥0.25-<1%

(Contd. on page 3)

Printing date 17.03.2020 Version number 12 Revision: 17.03.2020

Trade name HK-LASUR / HK Stain

((Contd.	of	page	2
	٧.	≤1	%	

		Contd. of page 2)
CAS: 22464-99-9 EINECS: 245-018-1 Reg.nr.: 01-2119979088-21-XXXX	2-ethylhexanoic acid, zirconium salt Repr. 2, H361d	≤1%
CAS: 55406-53-6 EINECS: 259-627-5 Index number: 616-212-00-7	3-iodo-2-propynyl butylcarbamate Acute Tox. 3, H331; STOT RE 1, H372; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1); Acute Tox. 4, H302; Skin Sens. 1, H317	≥0.25-<1%
CAS: 96-29-7 EINECS: 202-496-6 Index number: 616-014-00-0 Reg.nr.: 01-2119539477-28-XXXX	2-butanone oxime Carc. 2, H351; Eye Dam. 1, H318; Acute Tox. 4, H312; Skin Sens. 1, H317	≥0.1-≤0.5%
CAS: 64742-94-5 EINECS: 265-198-5 Index number: 649-424-00-3	Solvent naphtha (petroleum), heavy arom. Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336	<0.5%
CAS: 2372-82-9 EINECS: 219-145-8	N-(3-aminopropyl)-N-dodecylpropane-1,3-diamine Acute Tox. 3, H301; STOT RE 2, H373; Skin Corr. 1A, H314; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1)	<0.025%
CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2 Reg.nr.: 01-2119489379-17-XXXX	titanium dioxide Carc. 2, H351	≥0-≤10%

Additional information

Benzene content: < 0,1% Note P is applicable. It is not necessary to classify nor to mark the product as carcinogenic.

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

After inhalation

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness bring patient into stable side position for transport.

After skin contact

Wash immediately with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact Rinse opened eye for several minutes under running water.

After swallowing Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

Headache

Dizziness

4.3 Indication of any immediate medical attention and special treatment needed

To avoid dermatitis (skin inflammation), use skin cream.

symptomatic treatment

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents

Foam

Water spray jet

Water mist

5.2 Special hazards arising from the substance or mixture

May be released in case of fire

Carbon monoxide (CO)

Carbon dioxide

Formation of toxic gases is possible during heating or in case of fire.

(Contd. on page 4)

Printing date 17.03.2020 Version number 12 Revision: 17.03.2020

Trade name HK-LASUR / HK Stain

(Contd. of page 3)

5.3 Advice for firefighters

Protective equipment:

Wear self-contained breathing apparatus.

Wear full protective suit.

Additional information

Cool endangered containers with water spray jet.

Collect contaminated fire fighting water separately. It must not enter drains.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources

Ensure adequate ventilation

6.2 Environmental precautions:

Do not allow to enter the ground/soil.

Prevent from spreading (e.g. by confining or oil barrier).

This product may not be allowed to reach surface water because it is toxic to aquatic enviroments.

Inform responsible authorities in case product reaches bodies of water or sewage system.

6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable containers.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Use only in well ventilated areas.

Information about protection against explosions and fires:

Fumes can combine with air to form an explosive mixture.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and containers: No special requirements.

Information on storage in a common storage facility: Store away from food.

Further information about storage conditions:

Store container in a well ventilated position.

Protect from frost.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about design of technical systems: No further data; see item 7.

8.1 Control parameters

Components with limit values that require monitoring at the workplace:

CAS: 136-52-7 cobalt(II) 2-ethylhexanoate

WEL Long-term value: 0.1 mg/m³

as Co; Carc, Sen

Additional information: The lists that were valid during compilation were used as a basis.

8.2 Exposure controls

Personal protective equipment

General protective and hygienic measures

Do not eat, drink or smoke while working.

Apply solvent-resistant skin protection preparation before beginning work.

Keep away from food, beverages and animal feed.

Wash hands before pauses and after work.

Respiratory equipment: Filter A/P2.

Protection of hands:

Solvent resistant gloves

Printing date 17.03.2020 Version number 12 Revision: 17.03.2020

Trade name HK-LASUR / HK Stain

(Contd. of page 4)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection: Safety glasses recommended during refilling.

Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

320 Holl 3. I Hysical and chemical properties		
9.1 Information on basic physical and chemical properties General Information		
Appearance: Form: Colour: Odour: Odour threshold:	Liquid Different, according to dye Solvent-like Not determined.	
pH-value:	Not determined.	
Change in condition Melting point/freezing point: Initial boiling point and boiling range:	Not determined Not determined	
Flash point:	> 60 °C	
Inflammability (solid, gaseous)	Not applicable.	
Ignition temperature:	not applicable	
Decomposition temperature:	Not determined.	
Self-inflammability:	Product is not self-igniting.	
Explosive properties:	Product is not explosive.	
Explosive Limits: Lower: Upper:	0.6 Vol % 7.0 Vol %	
Vapour pressure:	Not determined.	
Density at 20 °C: Relative density Vapour density Evaporation rate	0.85±0.03 g/cm³ Not determined. Not determined. Not determined.	
Solubility in / Miscibility with Water:	Not miscible or difficult to mix	
Distribution coefficient (n-octanol/water): Not determined.		
Viscosity: dynamic: kinematic at 20 °C:	Not determined. 16 +/-2 s (DIN 53211/4)	
Solvent separation test	< 3 %	
VOC EU	< 400 g/l	

Printing date 17.03.2020 Version number 12 Revision: 17.03.2020

Trade name HK-LASUR / HK Stain

(Contd. of page 5)

9.2 Other information

No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if handled and stored according to specifications.

10.3 Possibility of hazardous reactions

Used empty containers may contain product gases which form explosive mixtures with air

- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity: Based on available data, the classification criteria are not met.

LD/LC50	LD/LC50 values that are relevant for classification:		
isoparaffi	isoparaffine hydrocarbon mixture		
Oral	LD50	>5,000 mg/kg (rat)	
Dermal	LD50	>5,000 mg/kg (rat)	
Inhalative	LC50/4 h	>20 mg/l (rat)	

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/irritation: Based on available data, the classification criteria are not met.

Sensitisation: Based on available data, the classification criteria are not met.

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met. STOT-single exposure: Based on available data, the classification criteria are not met. STOT-repeated exposure: Based on available data, the classification criteria are not met.

Aspiration hazard:

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: No further relevant information available.

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

Ecotoxical effects: Remark: Harmful to fish

Additional ecological information:

General notes:

Do not allow product to reach ground water, bodies of water or sewage system, even in small quantities.

Hazardous to drinking water even if extremely small quantities leak into soil.

Harmful to aquatic organisms

12.5 Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

Recommendation

Liquid material remains are to be disposed of at collection facilities for old varnishes.

The given refuse codes are recommendations based upon the intended use of the product. Because of special use and disposal conditions at the user's, other codes may apply under other conditions.

(Contd. on page 7)

Printing date 17.03.2020 Version number 12 Revision: 17.03.2020

Trade name HK-LASUR / HK Stain

(Contd. of page 6)

Europear	n waste catalogue		
03 02 02*	organochlorinated wood preservatives		

Uncleaned packaging:

Recommendation:

Disposal must be made according to official regulations.

Packaging can be reused or recycled after cleaning.

SECTION 14: Transport information

14.1 UN-Number ADR, ADN, IMDG, IATA	Void	
14.2 UN proper shipping name ADR, ADN, IMDG, IATA	Void	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA Class	Void	
14.4 Packing group ADR, IMDG, IATA	Void	
14.5 Environmental hazards: Marine pollutant:	No	
14.6 Special precautions for user	Not applicable.	
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.		
Transport/Additional information:	Not a hazardous good according to the above regulations.	
UN "Model Regulation":	Void	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

National regulations

Other regulations, limitations and prohibition ordinances

Do not use this wood preservative on wood that could come in direct contact with food or animal feed. Wood preservatives contain biocidal ingredients to protect wood from pests. They should only be used according to directions and only in the approved areas where protective measures are required. Misuse may harm your health and the environment.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Delivery specifications are found in the respective Technical Information Sheets.

This data is based on our present state of knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally valid contractual relationship.

Relevant phrases

- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.

(Contd. on page 8)

Printing date 17.03.2020 Version number 12 Revision: 17.03.2020

Trade name HK-LASUR / HK Stain

(Contd. of page 7)

H331 Toxic if inhaled.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

H361d Suspected of damaging the unborn child.

H361f Suspected of damaging fertility.

H372 Causes damage to organs through prolonged or repeated exposure.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

Classification according to Regulation (EC) No 1272/2008 Calculation method

Department issuing data specification sheet: Product Safety department / EHS Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - oral - Category 4

Acute Tox. 3: Acute toxicity - inhalation - Category 3

Skin Corr. 1A: Skin corrosion/irritation - Category 1A

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation - Category 1

Carc. 2: Carcinogenicity - Category 2

Repr. 2: Reproductive toxicity – Category 2 Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3